
Product data sheet
Characteristics

NSYSPF8200
Spacial SF/SM front plinth - 200x800 mm



Main

Range	Spacial
Accessory / separate part category	Enclosure accessory
Product or component type	Plinth front
Device application	Compartmentalised application Multi-purpose Electronic application
Enclosure nominal dimensions	-
Device composition	2 front panel 2 rear panel 4 corner 4 corner cover Fixing elements
Range compatibility	Spacial CRN Spacial S3D Spacial SF Spacial SM Spacial SD
Mounting support	Plinth side panels

Complementary

Fixing mode	By fixing element - on structure location
Colour	Grey RAL 7022
Surface finish	Epoxy-polyester powder
Permanent permissible load	1300 kg
Height	200 mm
Width	Nominal : 800 mm

Environment

IP degree of protection	IP30 complete plinth
IK degree of protection	IK10

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available Product environmental
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months